

NEW BRIO TANK



RESET AUTOMATICO
AUTOMATIC RESET

PROTEZIONE ANTIBLOCAGGIO 24H
24 HOURS ANTI-BLOCK PROTECTION

AUTORESET (OPTIONAL)	
TEST N°	STOP
01	5 min.
02	10 min.
03	20 min.
04	40 min.
05	60 min.
06	60 min.
07	60 min.
08	60 min.
09	60 min.
10	60 min.



ALIMENTAZIONE
POWER SUPPLY

230V 50 - 60 Hz



CORRENTE MAX
MAX RATED CURRENT
12A



PRESSIONE DI INTERVENTO
STARTING PRESSURE
1 - 3,5 bar



TARATURA DI FABBRICA
FACTORY SETTING
1,5 bar



GRADO DI PROTEZIONE
PROTECTION DEGREE
IP 65



PRESSIONE MAX AMMISSIBILE
(NON REGOLABILE)
MAX ALLOWABLE PRESSURE
(NOT ADJUSTABLE)
10 bar



PRESSIONE PRE-CARICA VASO
PRE-CHARGE PRESSURE TANK
1,5 bar



VASO DI ESPANSIONE
0,4LT MEMBRANA BUTILE
0,4 LT INTEGRATED PRESSURE
TANK WITH BUTYL BLADDER

