

Digital flow and pressure controller **BRIO TOP**



POWER SUPPLY:
115-230V, 50-60HZ



MAX RATED CURRENT:
16 A



FUNCTIONING: **FLOW AND
PRESSURE CONTROLLER** or
DIGITAL PRESSURE SWITCH



FACTORY SETTING:
1,5 BAR



PROTECTION DEGREE:
IP65



MAX RATED PRESSURE:
10 BAR

SERVICE FEATURES:

- Pump Working Counterers (time, starts)
- Error Log

AUXILIARY CONNECTION

For connection in twin booster sets,
remote control systems and/or float switch

PROTECTIONS:

- Pump Overload
- Pump Rotor Antilocking
- Pump Continuous restarting
- Anti-freezing

CAPACITOR COMPARTMENT
for installations with
submersible pumps

2 DIFFERENT SELECTABLE MODES OF USE:

1. **AUTOMATIC FLOW AND
PRESSURE CONTROL MODE (P+F)**
Adjustment range of starting
pressure 0,5-8 bar
2. **PRESSURE SWITCH MODE (P+P)**
Adjustable starting pressure 0,5 – 8 bar
Adjustable stopping pressure 0,8 - 9 bar
Minimum differential 0,3 bar



INSPECTIONABLE CHECK VALVE

1" 1/4 - 1"

1" 1/4 - 1" 1/4